

Premium oil based corrosion preventive compound

Tectyl 915W40 is an API CH-4/SJ SAE 15W-40 corrosion preventive, internal combustion engine oil, meeting the corrosion properties of MIL-L-21260. Tectyl 915W40 is an excellent preservative and break-in oil for reciprocating spark-ignition and compression-ignition engines in all types of ground equipment.

Approvals / Performance Levels

Tectyl™ 915W40	
Mil L 2104	PASS
Mil L 21260	PASS
MIL-L-46152 Military Specification	PASS
MIL-PRF-21260E Military Specification	PASS
API CH-4/SJ SAE 15W-40	PASS

Applications

Application

Tectyl 915W40 should be used as factory fill and break-in oil for all new and rebuilt engines. This is a completely operational oil for current production engine meeting the requirements of MIL-L-21260D and need not be changed until the first scheduled oil change specified by the engine manufacturer.

Features & Benefits

Lubricating oil with military properties

Tectyl 915W40 is a lubricating internal combustion oil, meeting the corrosion properties of MIL-L-21260, L-2104 and L-46152.

Trusted since 1930

Since 1930, Tectyl™ protective coatings have been extending the operational life of cars, trucks, buses and other vehicles and equipment. The Tectyl name is synonymous with quality coatings that are easy to apply, long-lasting and easy to remove when no longer required.

For more information on Tectyl products, programs and services please visit www.tectyleurope.com.

Health & Safety

This product is not likely to present any significant health or safety hazards when properly used in the recommended application and good standards of personal hygiene are maintained. Reference is made to the Safety Data Sheet (SDS) which is available on request via your local sales office.

Protect the environment

Comply with local regulations. Do not discharge into drains, soil or water.

Typical Properties

Typical property characteristics are based on current production. Whilst future production will conform to Tectyl specifications, variations in these characteristics may occur.

Tectyl™ 915W40	
Storage Temperature	10 - 35°C
Application Temperature	10 – 35°C
TBN ASTM D 2896	9.7 mg KOH/g
Viscosity Index ASTM D 2270	123
Viscosity ASTM D 445 @ 40°C	106 mm²/s
Viscosity ASTM D 445 @ 100°C	14.3 mm²/s
Specific Gravity ASTM D 4052 @ 15.6°C	0.885
Viscosity (CCS) ASTM D 5293 @ -20°C Max	7000 mPa·s

Storage

Tectyl 915W40 should be stored at temperatures between 10-35 °C. Do not freeze Tectyl 915W40. Mild agitation is recommended prior to use. Under proper storage conditions Tectyl 915W40 is best before 36 months after production date.

Caution

Adequate ventilation is required for cure and to ensure against formation of combustible liquid. Refer to the Safety Data Sheet for additional handling and first aid information.

Note

The addition of any product over this coating is not possible. The use of additional oil or coating could result in chemical incompatibility, thus affecting the performance of this oil as stated in the Performance level. If any other product, oil or coating, than a CorPro recommended product is required, written authorization must be obtained from CorPro.

State of the information

July 08, 2026

Validity

This information only applies to products manufactured in the following regions: Europe



<https://tectyleurope.com>