Tectyl™ 930

Premium oil based corrosion preventive compound

Tectyl 930 is an API CH-4/SJ SAE 30 corrosion preventive, internal combustion engine oil, meeting the corrosion properties of MIL-L-21260. Tectyl 930 is an excellent preservative and break-in oil for reciprocating spark-ignition and compression-ignition engines in all types of ground equipment.

Approvals / Performance Levels

Tectyl™ 930	
MIL-L-2104	PASS
MIL-L-21260	PASS
MIL-L-46152 Military Specification	PASS
MIL-PRF-21260E Military Specification	PASS
API CH-4/SJ SAE 30	PASS

Applications

Application

Tectyl 930 should be used as factory fill and break-in oil for all new and rebuilt engines. This is a completely operational oil for current production engine meeting the requirements of MIL-L-21260D and need not be changed until the first scheduled oil change specified by the engine manufacturer.

Features & Benefits

Lubricating oil with military properties

Tectyl 930 is a lubricating internal combustion oil, Meeting the corrosion properties of MIL-L-21260 MIL-2104 and MIL-L-46152.

Trusted since 1930

Since 1930, Tectyl™ protective coatings have been extending the operational life of cars, trucks, buses and other vehicles and equipment. The Tectyl name is synonymous with quality coatings that are easy to apply, long-lasting and easy to remove when no longer required.

For more information on Tectyl products, programs and services please visit www.tectyleurope.com.

Health & Safety

This product is not likely to present any significant health or safety hazards when properly used in the recommended application and good standards of personal hygiene are maintained. Reference is made to the Safety Data Sheet (SDS) which is available on request via your local sales office.

Protect the environment

Comply with local regulations. Do not discharge into drains, soil or water.

CORPRO

CorPro GmbH
Düsseldorfer Straße 40a
65760 Eschborn
Germany

+49 6196 56100-0
+49 (0)6173 9373-30
info@corpro.gmbh
corpro.gmbh

tectyleurope.com

™ Trademark of CorPro, registered in various countries © 2022

Tectyl™ 930

Typical Properties

Typical property characteristics are based on current production. Whilst future production will conform to Tectyl specifications, variations in these characteristics may occur.

Tectyl™ 930	
Flash Point (COC) Cleveland Open Cup	236°C
Storage Temperature	10 - 35°C
TBN ASTM D 2896	10.1 mg KOH/g
Viscosity ASTM D 2896	10.1
Viscosity ASTM D 2896	10.1 mg KOH/g
Viscosity Index ASTM D 2270	101
Viscosity ASTM D 445 @ 40°C	99 mm²/s
Viscosity ASTM D 445 @ 100°C	11.4 mm²/s
Specific Gravity ASTM D 4052 @ 15.6°C	0.889
Viscosity (CCS) ASTM D 5293 @ -15°C	6600 mPa·s

https://tectyleurope.com

Storage

Tectyl 930 should be stored at temperatures between 10-35 °C. Do not freeze Tectyl 930. Mild agitation is recommended prior to use. Under proper storage conditions Tectyl 930 can have a shelf life of 36 months minimum.

Caution

Adequate ventilation is required for cure and to ensure against formation of combustible liquid. Refer to the Safety Data Sheet for additional handling and first aid information.

Note

The addition of any product over this coating is not possible. The use of additional oil or coating could result in chemical incompatibility, thus affecting the performance of this oil as stated in the Performance level. If any other product, oil or coating, than a CorPro recommended product is required, written authorization must be obtained from CorPro.

State of the information

November 09, 2026

Validity

This information only applies to products manufactured in the following regions: Europe

CorPro GmbH
Düsseldorfer Straße 40a
65760 Eschborn
Germany

+49 6196 56100-0
+49 (0)6173 9373-30
info@corpro.gmbh
corpro.gmbh

tectyleurope.com
TM Trademark of CorPro, registered in various countries © 2022